


“CLEANING THE WORLD WITH ACTIVATED CARBON”



GC 8 X 30PF

Granular activated carbon for PFOS and PFAS treatment

GC 8 X 30PF is a re-agglomerated activated carbon manufactured from a specially selected grade of bituminous coal. Manufactured at an NSF/ANSI certified facility, it is suitable for drinking water and food grade applications. It is specially formulated for the removal of emerging contaminants like PFOS and PFAS.

Specifications

US Mesh Size:	90 (min)
On 8 US Mesh, %:	5 (max)
Through 30 US Mesh, %:	4 (max)
Typical Ash Content, %:	12-13
Moisture, % (as packaged):	5 (max)
Iodine, mg/g:	1000 (min)
Surface Area, m ² /g:	950 (min)
Hardness, %:	90 (min)
Abrasion Number:	80 (min)
Apparent Density, lbs./cu.ft:	24-26
g/cc:	0.40-0.42
pH:	9-11
Typical TCN	10-11

*Standard packaging is in 55lb and 1,100lb vinyl bags. Other packaging is available upon request with an additional cost.

Caution!

Wet activated carbon removes oxygen from air causing a severe hazard to workers inside carbon vessels. Confined space/low oxygen procedures should be put in place before any entry is made. Such procedures should comply with all applicable Local, State and Federal guidelines.

33 Paterson Street Paterson, NJ 07501 Tel: 973-523-2223 Fax: 973-523-1494

www.generalcarbon.com

sales@generalcarbon.com